

ACRYL FASSADENFARBE

Weather-resistant interior and exterior paint

WHITE



PACKAGING	CONSUMPTION	SHADE
3 L / 10 L	200–250 g/m ² per coat	White

PRODUCT DESCRIPTION

Titanium Acryl Fassadenfarbe is a high-build façade paint suitable for use in external thermal insulation composite systems (ETICS). It is water-vapour-permeable (breathable), high in build, weather-resistant and with good adhesion. Titanium Acryl Fassadenfarbe is tintable. Mode of action: Titanium Acryl Fassadenfarbe is a weather-resistant interior and exterior paint. It is easy to apply and gives uniform surfaces free of lap marks. Suitable for airless application. Quality control: internal quality control by our state-of-the-art laboratory. Binder base: acrylate. Gloss level: matt. Shade: base (W), (P), (T). Packaging sizes: 3 L, 10 L.

SUBSTRATE PREPARATION

Substrate: the substrate must be clean and dry in order to ensure high-quality processing. New substrates: remove soiling and clean, remove sintered layers if present. Old substrates: clean thoroughly, mechanically or with high pressure. Priming: with solvent-free Titanium Tiefgrund (consumption approx. 250 ml/m², depending on absorbency).

PRODUCT PREPARATION

Processing instructions: please observe the instructions on the back of the packaging. Intermediate coat: apply after approx. 6 hours with Titanium Acryl Fassadenfarbe diluted with 5–10 % water. Max. dilution 10 %. Finishing coat: apply undiluted, adding max. 5 % water if required.

APPLICATION

Overcoating: possible after approx. 3 hours, depending on temperature and humidity. Check the substrate for suitability. Consumption: approx. 200–250 g/m² per coat. Notes: a) Minimum drying time between coats: 6 hours (20 °C, 65 % RH). b) Low temperatures and high humidity extend drying. c) Application by roller or airless spray. d) Tinting with Titanium Color Mix. e) Dilute with water only. f) Clean tools with water immediately. g) Carry out test coats to determine the opacity. h) Dispose of with household waste once completely dry. Safety instructions: not subject to labelling under the Hazardous Substances Ordinance. Do not allow fresh paint to enter the sewer system.

TOOLS

Processing: application by brush, roller or airless spray.

STORAGE AND SHELF LIFE

Storage: store in a cool, frost-free place. Shelf life up to 24 months in the original packaging. Additional information: technical documentation and safety data sheet: www.titanium-baustoffe.de

TECHNICAL DATA

Form	Liquid
Colours	White
Application conditions	Standard parameters
Temperature	20 °C
Relative humidity	≤ 65 %
Application temperature	5–30 °C
pH value	8.0
Water vapour permeability	V1
Water permeability coefficient	W3
Consumption	200/250 g/m ²
Adhesion	1.5 N/mm ²
Packaging	3 L / 10 L
Shelf life	24 months from date of production

DECLARATION OF PERFORMANCE



TITANIUM
EN 1062-1:2005

Manufacturer: REFIX SH.P.K. RKS
Declaration of Conformity 001/24.04.2026
Standard: EN 1062-1:2005

TITANIUM - Acryl Fassadenfarbe

Release of dangerous substances	see MSDS
Adhesion	≥ 1.5 N/mm ²
Water absorption	≥ category Wc1 - low
Water vapour diffusion coefficient	Class V1 - high
Drying time	2 hours
Gloss	Class G4 - matt