

SUPER FINISH

Fine skim coat for interiors

WHITE COLOUR

EXTRA WHITE



UNIT	PIECES/PALLET	CONSUMPTION	COLOUR/FURTHER SPECIFICATIONS
20 kg/bag	48 pieces/pallet	8.5–9 l/20 kg	White colour

PRODUCT DESCRIPTION

SUPER FINISH is a fine skim coat material with a very fine grain size, suitable exclusively for interior use.

ADVANTAGES

Easy to prepare and apply. Extremely white. Suitable for interior use only.

FIELDS OF APPLICATION

SUPER FINISH is used for smoothing walls and ceilings in dry interior rooms without moisture. Suitable for smooth substrates such as concrete and FINO, and very well suited to plasterboard. The final result on wall and ceiling is extremely white and smooth.

SUBSTRATE PREPARATION

The substrate must be firm, level, clean and dry. On old substrates it is advisable to pre-treat the surface with a suitable primer / base. The air and substrate temperature during application and drying should be between +5 °C and +30 °C.

PRODUCT PREPARATION

The product must be mixed in a clean container. The contents of a 20 kg bag are added gradually to 8.5–9 litres of water and stirred with an electric mixer to a homogeneous, lump-free mass.

APPLICATION

The prepared mass must be applied with a steel trowel within 50 minutes of preparation, in one or two coats with a maximum thickness of 1–1.5 mm per coat. For the second coat, wait until the first has dried completely. Once fully dry, the surface can be smoothed with fine abrasive paper if required, in order to achieve a uniform and smooth appearance. The drying time may vary depending on the weather conditions and the ventilation of the room.

PRODUCT SAFETY

According to CPL regulations this product is considered non-hazardous. General safety measures must nevertheless be observed: avoid prolonged contact with skin or eyes. In case of eye contact, rinse immediately and thoroughly with plenty of water. Wear protective equipment (FFP2 mask, gloves in accordance with EN 374-1 and safety goggles). Keep away from unprotected persons. Avoid the formation of dust. Ensure adequate ventilation. Do not eat or drink while working. Wash hands thoroughly before and after work. Keep away from children.

STORAGE AND SHELF LIFE

12 months; store on pallets in dry areas, protected from the weather. Protect from frost.

ADDITIONAL INFORMATION

Technical documentation and the safety data sheet are available on the official website: www.titanium-baustoffe.de

Standard: EN 998-1:2016 · GP-CS II · Wc2

The information in this data sheet reflects the current state of the art and has been compiled to the best of our knowledge. It does not constitute warranted characteristics and does not release the applicator from testing the product's suitability for the intended purpose. This edition supersedes all previous versions.

TECHNICAL DATA

Form	Powder
Colour	White
Density	8.5–9.0 l / 20 kg
Application temperature	+5 °C to +30 °C
Compressive strength	3.2 N/mm² (Class CS III)
Capillary water absorption	0.09 kg/m²·h^{0.5} (Category Wc1)
Tensile adhesion strength	0.80 N/mm²
Thermal conductivity	0.65 W/m·K

DECLARATION OF PERFORMANCE



TITANIUM
EN 998-1:2016

Manufacturer: REFIX SH.P.K. RKS
DOP -206-1/05.12.2025
Standard: EN 998-1:2016

TITANIUM-SUPER FINISH

Compressive strength	≥ 3.2 N/mm²
Capillary water absorption	W1
Adhesion	0.80 N/mm²
Thermal conductivity	0.65 W/m·K